



US006946645B2

(12) **United States Patent**
Tarvin et al.

(10) **Patent No.:** US 6,946,645 B2
(45) **Date of Patent:** Sep. 20, 2005

(54) **MEASURING SYSTEM WITH SWEEPING COMB FILTER AND MULTIPLEXER**

(75) Inventors: **Jeffrey A. Tarvin**, Brookfield, CT (US); **Robert J. Schroeder**, Newtown, CT (US); **Rogério T. Ramos**, Chandlers Ford (GB); **Tsutomu Yamate**, Yokohama (JP)

(73) Assignee: **Schlumberger Technology Corporation**, Ridgefield, CT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 98 days.

(21) Appl. No.: **10/733,531**

(22) Filed: **Dec. 11, 2003**

(65) **Prior Publication Data**

US 2004/0178330 A1 Sep. 16, 2004

Related U.S. Application Data

(63) Continuation-in-part of application No. 09/741,225, filed on Dec. 20, 2000, now abandoned.

(51) **Int. Cl.**⁷ **G01B 11/16**

(52) **U.S. Cl.** **250/227.14; 250/227.18**

(58) **Field of Search** **250/227.14, 227.16, 250/227.18, 227.21, 227.23; 382/12, 13, 37; 356/32**

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,834,493 A	5/1989	Cahill et al.	350/96.2
5,118,931 A	6/1992	Udd et al.	250/227.16
5,397,891 A *	3/1995	Udd et al.	250/227.18
5,818,585 A	10/1998	Davis et al.	356/345
5,828,059 A	10/1998	Udd	250/227.18

5,841,131 A	11/1998	Schroeder et al.	250/227.17
6,115,121 A	9/2000	Erskine	356/345
6,380,534 B1	4/2002	Farhadiroushan et al.	250/227.14
6,449,047 B1	9/2002	Bao et al.	356/478

OTHER PUBLICATIONS

Schroeder, Robert J. and Yamate, Tsutomu. *High Pressure and Temperature Sensing for the Oil Industry Using Fiber Bragg Gratings Written Onto Side Hole Single Mode Fiber. Presented at 13th Int'l Conf. on Optical Fiber Sensors* (Apr. 12-16, 1999).

* cited by examiner

Primary Examiner—Edward J. Glick

Assistant Examiner—Chih-Cheng Glen Kao

(74) *Attorney, Agent, or Firm*—John Lee; Jody Lynn DeStefanis; Dale Gaudier

(57) **ABSTRACT**

High-resolution measurement of a parameter is provided at multiple different locations simultaneously along an optic fiber. Light within a predefined range of wavelengths is transmitted into an optic fiber that contains multiple birefringent fiber optic pressure transducers, each including a Fiber Bragg Grating. Each grating defines a spatially modulated index of refraction and a wavelength that is unique within the system. A sweeping comb filter is used to apply optical comb filtering to light reflected from the transducers so as to pass filtered light having multiple spectral portions, each spectral portion associated with one transducer. The free spectral range of the sweeping comb filter is set to be approximately equal to the spectral range of a single spectral portion. Wavelength division multiplexing is applied to the filtered light so as to separate the spectral portions. The value of a parameter is preferably determined using the spectral spacing of two maxima of spectral intensity in each spectral portion.

17 Claims, 6 Drawing Sheets

